

Rosholt Black Top Tractor Pull Rules

1. Tractors must be operated in a safe manner at all times. Anyone driving recklessly or caught tampering with another person's tractor will be disqualified from pulling.
2. One pull allowed per tractor in each class unless the track judge rules otherwise or if a tie is declared in the top placing tractors. If disqualification is ruled on top placing tractor, all other tractors move up one place.
3. Any tractor violating the track boundary will be disqualified. The decision of the track judge will be final.
4. Drivers must be 14 years of age or older. All drivers enter at own risk. Drivers between the age of 14 and 18 must have parent's written consent and safety class certificate with them. NO EXCEPTIONS!!!
5. Tractors will be stopped if the frond end raises higher than the track judge decides is safe.
6. Extra weights must be securely fastened to the tractor. If anything falls off before the pin is pulled, the tractor will be disqualified.
7. Any gas-operated tractor must use gasoline only.
8. While pulling the driver must remain on the seat (if so equipped) with one hand on the wheel. No jumping or bouncing will be allowed, however, leaning will be permitted.
9. Tractors must stop immediately upon red flag signal from the judge or be disqualified. If puller is stopped by track judge for any reason, puller takes the distance where he/she stopped except if it is the first ten feet. If stopped within the first ten feet, puller is entitled to a restart.
10. Tractors must be wheel driven, no crawlers or dual wheels, NO FWD.
11. Puller must furnish own clevis or pullers' eye to accept eliminators hook. (MINIMUM 2.5" HOLE. PULLING POINT CAN BE NO MORE THAN 1.5" FROM THE BACK EDGE OF HITCHING DEVICE.)
12. Tractors with draw bar closer than 32" to center of rear axle must have wheelie bars, kill switch and fenders.

CLASSIC

1. Must be 1957 and older paced at 3.7.
2. Weight classes: 3500, 4200, 4700, 5500, 6500, 7500 and 8500.
Max tire size: 3500-4700: 14.9" x 38" or 15.5" x 38"
5500: 16.9" x 38"
6500-8100: 18.4" x 38"
3. Front weights shall not exceed more than 24" beyond the center of the front frames outmost casting. Rear weights not to exceed 24" behind center rear axle.
4. Rigid draw bar must not exceed 20" in height, nor can be closer than 18" from the center of the rear axle.
5. Engine speed must be controlled by the throttle lever and a functional stock governor only. No strings, wires or foot feeds allowed. Decision of the track judge is final. 20% over RPMS will be allowed. ALL TRACTORS RPM LIMITS ENFORCED.