

Weight classes: 3000, 4000, 5000, 6000, 7000, and 12000.

Max tire size: 3000 – 13.6”

4000 – 15.5”

5000 – 16.9”

6000, 7000, 12000 – 18.4”

2. Front weights shall not exceed more than 24” beyond the center of the front frames outmost casting. Rear weights not to exceed 24” behind center rear axle.
3. Rigid draw bar must not exceed 20” in height, nor can be closer than 18” from the center of the rear axle.
4. Engine speed must be controlled by the throttle lever and a functional stock governor only. No strings, wires or foot feeds allowed. Decision of the track judge is final. 20% over RPMS will be allowed. ALL TRACTORS RPM LIMITS ENFORCED.

NEAR STOCK

1. Must be 1957 or older – low gear only.
Weight classes: 4000, 5000, 6000, and 7000. Must be within manufactures hp and RPMS.
2. Engine, stock block, head, manifold, carb (by part #), no add-on parts not in original parts book. No electronic ignitions, stock coil only. Stock hp and rpms.
3. Tractors must have original, or as close to original size tires, rims, cut-down steel is ok. No 18.4” tires will be allowed.
4. Original hitch/drawbar hole must be no closer than 32” from center of rear axle, allowances will be made on certain models, maximum height 20” and must be rigid.
5. Tractors must have stock appearance.
6. No cut or sharpened tires.
7. Must have original air cleaner, if one is used.
8. No weight brackets. Weights will only be allowed if placed on wheels.
9. No radial tires.
10. ALL TRACTORS WILL BE DYON’ED AND RPM LIMITS WILL BE ENFORCED.

8 MPH PACE

1. Must be 1957 or older.
Weight classes: 3750, 4750, 5750, 6750.
Max tire size: 18.4”
2. Must run stock block, transmission, rear-end, sheet metal, etc.
3. Cut tires are allowed.
4. Wheelie bars, kill switch and fenders MANDATORY!
5. RPM’s over 20% must have safety equipment (safety blanket, scatter shield, steel flywheel, fan shroud or side shields, etc.)
6. NO TROPHIES, 100% PAYBACK FOR FIRST, SECOND and THIRD PLACING.

Rigid draw bar MUST
support weight of tractor